

Option Availability

Mechanical

Symbol	Description	Remark
DOM	Dome indicator	Except for Mdl. 0020, 0050
EX	Explosion proof (Ex d II B'(C) T4)	Except for Mdl. 0020, 0050
WT	Watertight (IP68)	Except for Mdl. 0020, 0050
ALS	Auxiliary limit switches (Max 4 for each travel end)	
ATS	Auxiliary torque switches (Max 4 for each travel end)	Except for Mdl. 0020,0050,0080
EXT	Extended travel angle (upto 120°, 135°, 180°, 270°)	Except for ITQ with Gear Box
SV	Variation in torque and operating speed	Please consult before order

Remote monitoring and control

PK	Potentiometer kit (output signal: 0~1 Kohm)	
CT	Current transmitter (output: 4-20mA)	
RPC	Remote position controller (by input and output signal)	Refer to below signal configuration
RPD	Remote position controller (by input and output signal) with display (LCD)	
Signal	Input: 4-20mA, 0-10VDC, 2~10VDC, 1~5VDC, 0~5VDC	
Configuration	Output: 4-20mA, 0-10VDC, 2~10VDC, 1~5VDC, 0~5VDC	

Local monitoring and control

LP 1	Local position control (Remote / Open / Stop / Close without lamps)
LP 2	Local position control (Remote / Local, Open / Stop / Close without lamps)
LM 1	Integrated motor starter without local switches (On-Off only)
LM 2	Local position control (Remote / Local, Open / Stop / Close without lamps)
	integrated motor starter (Mechanical)
LD	Local position control (Remote / Local / Open / Stop / Close
	with lamps) with integrated motor starter, monitoring relays

Intelligent

IT-Pak (Intelligent)	LD pack with intelligent functions Auto calibration, Self Diagnosis, Profibus protocol and display	Available 2004
-------------------------	---	----------------